

# Technical data sheet

LG 60 cable ladder, 3 m VSF FT

Item number: 6207542



Cable ladder for horizontal routing of cables. Can be used in the widths 200–400 mm as a standard support structure for the maintenance of electrical functionality according to DIN 4102 Part 12. Maintenance of electrical functionality classes E30 to E90. With riveted C profile rung, open in an upward direction.

E30 E60 E90

St Steel

FT Hot-dip galvanised

## Master data

|                                   |                              |
|-----------------------------------|------------------------------|
| Item number                       | 6207542                      |
| Type                              | LG 640 VSF 3 FT              |
| Description 1                     | Cable ladder function maint. |
| Description 2                     | rungs distance 150 mm        |
| Manufacturer                      | OBO                          |
| Dimension                         | 60x400x3000                  |
| Colour                            | zinc                         |
| Material                          | Steel                        |
| Surface                           | Hot-dip galvanised           |
| Surface standard                  | DIN EN ISO 1461              |
| Smallest sales unit               | 3                            |
| Unit of quantity                  | Metre                        |
| Weight                            | 425.2 kg                     |
| Weight unit                       | kg/100 m                     |
| CO Footprint (GWP) Cradle-to-Gate | 10,0331 kg COe / 1 Meter     |


# Technical data sheet

LG 60 cable ladder, 3 m VSF FT

Item number: 6207542



## Dimensions



|                     |          |
|---------------------|----------|
| Length              | 3,000 mm |
| Width               | 400 mm   |
| Height              | 60 mm    |
| Dimension B         | 400 mm   |
| Rung slot dimension | 17.00    |

## Technical data

|                               |                       |
|-------------------------------|-----------------------|
| Version of the rungs          | Profile perforated    |
| Side rail version             | Profile (open)        |
| Fastening of rung             | Blind riveted         |
| Maintain electrical functions | yes                   |
| Usable cross-section          | 19800 mm <sup>2</sup> |
| Rustproof steel, pickled      | no                    |
| Side perforation              | yes                   |
| Rung distance                 | 150 mm                |
| Wide-span version             | no                    |
| Rail thickness                | 1.5 mm                |