Technical data sheet

Gutter clamp RK-FIX A2

Item number: 5316459



- For up to 2 round conductors Rd 6 or Rd 8
- Suitable for all bead thicknesses (15–25 mm)
- With 1 truss-head bolt M10 x 45
- With spring for prefixing on rain gutter
- Clamp body and crossbar made of rustproof stainless steel (V2A)
- Nut, bolt and spring made of stainless steel (V2A)
- Tested to VDE 0185-561-1 (IEC/EN 62561-1)

A2 Stainless steel

Master data


Item number	5316459
Type	RK-FIX VA
Description 1	Gutter clamp with spring
Manufacturer	OBO
Dimension	2x8 / 2x6mm
Material	Stainless steel 1.4301
Smallest sales unit	10
Unit of quantity	Piece
Weight	19.1 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,2314 kg CO2e / 1 Piece


Technical data sheet

Gutter clamp RK-FIX A2

Item number: 5316459

Dimensions





Length	64.95 mm
Width	41 mm
Height	45 mm

Technical data

Type of fastening screw	Hexagonal bolt
Type of connector	Roof gutter clamp
Lightning current carrying capacity	H/100 kA
Fit	2 x Rd 8/ 2 x Rd 6 mm
ROHS-conformant	yes
Clamping range, max.	25 mm
Clamping range, min.	15 mm