# Technical data sheet

## Height-adjustable cassette for inspection opening, RKN, stainless steel
## Item number: 7408970



"Blank" height-adjustable cassette for the creation of an inspection opening of nominal size 4. Installation of devices in duct systems, raised and cavity floors in interior dry or wet-care floors. Only suitable for smooth floor coverings.
For the installation of three UT4 universal supports for nine single devices with support ring/support clamp or 12 Modul 45® devices. 3 APMT5 cover plates can be installed.

IP 55

A2 Stainless steel


### Master data


| | |
|---|---|
| Item number | 7408970 |
| Type | RKN3 9 VS 20 |
| Description 1 | Square cassette |
| Description 2 | Blank lid |
| Manufacturer | OBO |
| Dimension | 243x243x100 |
| Material | Stainless steel |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 360 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 20,3725 kg CO2e / 1 Piece |

# Technical data sheet

## Height-adjustable cassette for inspection opening, RKN, stainless steel
## Item number: 7408970

### Dimensions




| | |
|---|---|
| Length | 243 mm |
| Width | 243 mm |
| Height | 105 mm |
| Dimension h | 105 mm |

### Technical data

| | |
|---|---|
| Number of installable devices | 0 |
| Number of cable outlets | 0 |
| Number of universal supports | 3 x UT4 |
| Cover version | Square |
| Cable outlet version | No cable outlet |
| Floor cut-out / Mounting opening | 244x244 |
| Floor care | Wet |
| Decouplable | no |
| Floor height, max. | 150 mm |
| Floor height, min. | 105 mm |
| Suitable for raised floor installation | yes |
| Suitable for cavity floor installation | yes |
| Suitable for underfloor box | 250/350 |
| Device support to accept mounting boxes | no |
| Length of installation dimensions | 244 mm |
| Nominal size for device installation units | 9 |
| Height-adjustment range, max. | 150 mm |
| Height-adjustment range, min. | 105 mm |
| Standard | EN 50085-2-2 |
| ROHS-conformant | Exempt |
| Protection rating (IP) when used | IP00 |
| Protection rating (IP) when unused | IP55 |
| Protection rating IK code | IK10 |
| Heavy-duty version | no |
| Installation system type | UT4 |
| Vertical load, large area | to 5,000 N |
| Vertical load, small area | to 3,000 N |
| Approvals | VDE |
| Floor covering thickness | 20 mm |