Technical data sheet

Cable gland, PG thread, light grey

Item number: 2024705



Cable gland with PG connection thread in cap nut design, suitable for junction boxes, housings
With strain relief and integrated sealing lip, tested according to DIN EN 62444.
Protection class IP68. Can be used between –20 °C and +65 °C.
To prevent damage caused by differences in material behaviour, avoid using a mix of materials
Use products made from polyamide (cable glands) exclusively with polyamide accessory parts
lock nuts, reducers, expansions, etc.) Use products made from polystyrene exclusively with po

750° UV RESISTANT IP 68 Pg

PA Polyamide

Master data


Item number	2024705
Type	V-TEC PG7 LGR
Description 1	Cable gland
Manufacturer	OBO
Dimension	PG7
Colour	Light grey; RAL 7035
Material	Polyamide
Smallest sales unit	50
Unit of quantity	Piece
Weight	0.41 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,0223 kg CO2e / 1 Piece

Technical data sheet

Cable gland, PG thread, light grey

Item number: 2024705

Dimensions



Dimension E	16.5 mm
Dimension L max.	23 mm
Dimension L min.	18 mm
Dimension L1	8 mm
Dimension L2	5 mm
Dimension L3	12.6 mm

Technical data

Type of seal	Sealing ring
Version for	Straight
Bend protection	no
Sealing area D, max.	6.5 mm
Sealing area D, min.	2.5 mm
explosion-proof	no
Flat cable gland	no
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Thread	Pg 7
Thread type	PG
Thread length	8 mm
Nominal thread size	7
Thread increase	1.41 mm
Fibre-glass reinforced	no
Halogen-free	yes
Unstable torque	1.67 Nm
Sealing insert, multiple	no
With locknut	no
ROHS-conformant	yes
Impact-resistant	no
WAF	15
Protection rating	IP68
Hexagonal corner dimension	16.5 mm
Splittable gland	no

Technical data sheet

Cable gland, PG thread, light grey

Item number: 2024705

Technical data

Permitted temperature range, max.	65 °C
Permitted temperature range, min.	-20 °C
Strain relief and wringing protection D2, max.	6.5 mm
Strain relief and wringing protection D2, min.	3 mm
Strain relief option	yes